

ABRAFLAT /4

LAYFLAT CEMENT HOSE



APPLICATION

Layflat delivery hose for concrete, sand, gravel and general abrasive dry materials

TUBE

Black, smooth, **NR/SBR** antistatic rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, antistatic cloth impression **SBR/NR/PVC** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-40°F +158°F
-40°C +70°C

SPECIFICATIONS

DIN 53516 70 ± 5mm3

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
90	3 35/64	100	3 15/16	1.25	4	60	12	180	40/61
102	4	112	4 13/32	1.39	4	60	12	180	40/61
110	4 21/64	120	4 23/32	1.52	4	60	12	180	40/61
127	5	137	5 25/64	1.72	4	60	12	180	40/61
152	6	162	6 3/8	2.05	4	60	12	180	40/61
203	8	213	8 25/64	2.74	4	60	12	180	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

