

# ABRAFLEX SD/10

CEMENT SUCTION AND DELIVERY HOSE HELIX GROOVED COVER



## APPLICATION

Suction and delivery hose for concrete, sand, gravel and general abrasive materials. The outside corrugation assures an outstanding flexibility

## TUBE

Black, smooth, **NR/SBR** antistatic rubber compound

## REINFORCEMENT

High strength synthetic plies with steel wire spirals

## COVER

Black, helix grooved, antistatic cloth impression **SBR/NR/PVC** rubber compound, abrasion and weather resistant

## WORKING TEMPERATURE

-40°F +158°F

-40°C +70°C

## SPECIFICATIONS

DIN 53516 50 ± 5mm<sup>3</sup>

ID		WEIGHT	WP		BP		BENDING RADIUS	VACUUM	COIL LENGTH
mm	inch	kg/m	bar	psi	bar	psi	mm	bar	m
51	2	1.80	10	150	30	450	153	0.9	40
60	2 3/8	2.10	10	150	30	450	180	0.9	40
63.5	2 1/2	2.30	10	150	30	450	285	0.7	40
70	2 3/4	2.50	10	150	30	450	315	0.7	40
76	3	2.90	10	150	30	450	340	0.7	40
80	3 5/32	3.30	10	150	30	450	360	0.7	40
90	3 35/64	3.60	10	150	30	450	405	0.7	40
102	4	4.80	10	150	30	450	450	0.7	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

## BRANDING

