

# ABRAMUD SW /10

DELIVERY HOSE FOR DRILLING MUDS



## APPLICATION

Delivery hose, for drilling oil rig hose services, for petroleum muds and crude oil

## TUBE

Black, smooth, **NBR/PVC** rubber compound

## REINFORCEMENT

High strength synthetic cord, with crossing copper wires for hose grounding

## COVER

Black, smooth cloth impression, **CR** rubber compound, resistant to oil, grease, sea water, ozone and flame retardant

## WORKING TEMPERATURE

-40°F +212°F  
-40°C +100°C

| ID  |      | OD  |         | WEIGHT | WP  |     | BP  |     | COIL LENGTH |
|-----|------|-----|---------|--------|-----|-----|-----|-----|-------------|
| mm  | inch | mm  | inch    | kg/m   | bar | psi | bar | psi | m           |
| 76  | 3    | 92  | 3 5/8   | 2.95   | 10  | 150 | 40  | 600 | 60          |
| 102 | 4    | 119 | 4 11/16 | 4.22   | 10  | 150 | 40  | 600 | 60          |
| 127 | 5    | 144 | 5 43/64 | 4.95   | 10  | 150 | 40  | 600 | 60          |
| 152 | 6    | 174 | 6 27/32 | 7.41   | 10  | 150 | 40  | 600 | 60          |
| 203 | 8    | 226 | 8 57/64 | 10.22  | 10  | 150 | 40  | 600 | 40          |
| 254 | 10   | 279 | 11      | 14.03  | 10  | 150 | 40  | 600 | 20          |
| 302 | 12   | 331 | 13 5/16 | 18.76  | 10  | 150 | 40  | 600 | 12          |

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

## BRANDING

