

# ABRAMUD SW /10

DELIVERY HOSE FOR DRILLING MUDS



## APPLICATION

Delivery hose, for drilling oil rig hose services, for petroleum muds and crude oil

## TUBE

Black, smooth, **NBR/PVC** rubber compound

## REINFORCEMENT

High strength synthetic cord, with crossing copper wires for hose grounding

## COVER

Black, smooth cloth impression, **CR** rubber compound, resistant to oil, grease, sea water, ozone and flame retardant

## WORKING TEMPERATURE

-40°F +212°F  
-40°C +100°C

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
76	3	92	3 5/8	2.95	10	150	40	600	60
102	4	119	4 11/16	4.22	10	150	40	600	60
127	5	144	5 43/64	4.95	10	150	40	600	60
152	6	174	6 27/32	7.41	10	150	40	600	60
203	8	226	8 57/64	10.22	10	150	40	600	40
254	10	279	11	14.03	10	150	40	600	20
302	12	331	13 5/16	18.76	10	150	40	600	12

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

## BRANDING

