


# ABRAMUD SW /20

DELIVERY HOSE FOR DRILLING MUDS



## APPLICATION

Delivery hose, for drilling oil rig hose services, for petroleum muds and crude oil

## TUBE

Black, smooth, **NBR/PVC** rubber compound

## REINFORCEMENT

High strength synthetic cord, with crossing copper wires for hose grounding

## COVER

Black, smooth cloth impression, **CR** rubber compound, resistant to oil, grease, sea water, ozone and flame retardant

## WORKING TEMPERATURE

-40°F +212°F  
-40°C +100°C

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
76	3	96	3 25/32	3.70	20	300	80	1200	60
102	4	124	4 7/8	5.20	20	300	80	1200	60
127	5	153	6 5/32	7.40	20	300	80	1200	60
152	6	178	7	8.70	20	300	80	1200	60
203	8	227	8 15/16	10.80	20	300	60	900	40
254	10	285	11 7/32	17.20	20	300	60	900	20
302	12	337	13 17/64	22.50	20	300	60	900	12

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

## BRANDING

