

# ABRAPARA

NR RUBBER TUBING FOR ABRASIVE MATERIALS - NO PRESSURE



## APPLICATION

No pressure discharge hose, for silos and hopper, for abrasive materials as sand, gravel, cement, etc

## TUBE

Brown, smooth **NR** rubber compound, SHORE A 45

## COVER

Black, smooth cloth impression **NR** rubber compound, SHORE A 45

## WORKING TEMPERATURE

-40°F +158°F

-40°C +70°C

| ID  |          | OD  |          | WEIGHT | COIL LENGTH |
|-----|----------|-----|----------|--------|-------------|
| mm  | inch     | mm  | inch     | kg/m   | m           |
| 80  | 3 5/32   | 90  | 3 35/64  | 1.45   | 5           |
| 90  | 3 35/64  | 100 | 3 15/16  | 1.63   | 5           |
| 102 | 4        | 112 | 4 13/32  | 1.83   | 5           |
| 110 | 4 21/64  | 120 | 4 23/32  | 1.97   | 5           |
| 120 | 4 23/32  | 130 | 5 1/8    | 2.14   | 5           |
| 127 | 5        | 137 | 5 25/64  | 2.26   | 5           |
| 130 | 5 1/8    | 140 | 5 33/64  | 2.31   | 5           |
| 140 | 5 33/64  | 150 | 5 29/32  | 2.48   | 5           |
| 152 | 6        | 162 | 6 3/8    | 2.69   | 5           |
| 160 | 6 19/64  | 170 | 6 11/16  | 2.82   | 5           |
| 168 | 6 39/64  | 178 | 7        | 2.96   | 5           |
| 180 | 7 15/16  | 190 | 7 31/64  | 3.17   | 5           |
| 190 | 7 31/64  | 200 | 7 7/8    | 3.34   | 5           |
| 203 | 8        | 213 | 8 25/64  | 3.56   | 5           |
| 220 | 8 21/32  | 230 | 9 5/8    | 3.85   | 5           |
| 254 | 10       | 264 | 10 25/64 | 4.45   | 5           |
| 273 | 10 3/4   | 283 | 11 9/64  | 4.76   | 5           |
| 280 | 11 5/16  | 290 | 11 27/64 | 4.88   | 5           |
| 305 | 12       | 315 | 12 13/32 | 5.31   | 5           |
| 320 | 12 19/32 | 330 | 12 63/64 | 5.56   | 5           |
| 350 | 13 25/32 | 360 | 14 11/64 | 6.10   | 5           |
| 400 | 15 3/4   | 410 | 16 9/64  | 7.00   | 5           |
| 450 | 17 23/32 | 460 | 18 1/8   | 7.79   | 5           |
| 500 | 19 11/16 | 510 | 20 25/32 | 8.64   | 5           |
| 600 | 23 5/8   | 610 | 24 5/32  | 10.35  | 5           |

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.