

ABRAPARA

NR RUBBER TUBING FOR ABRASIVE MATERIALS - NO PRESSURE



APPLICATION

No pressure discharge hose, for silos and hopper, for abrasive materials as sand, gravel, cement, etc

TUBE

Brown, smooth NR rubber compound, SHORE A 45

COVER

Black, smooth cloth impression NR rubber compound, SHORE A 45

WORKING TEMPERATURE

-40°F +158°F

-40°C +70°C

ID		OD		WEIGHT	COIL LENGTH
mm	inch	mm	inch	kg/m	m
80	3 5/32	90	3 35/64	1.45	5
90	3 35/64	100	3 15/16	1.63	5
102	4	112	4 13/32	1.83	5
110	4 21/64	120	4 23/32	1.97	5
120	4 23/32	130	5 1/8	2.14	5
127	5	137	5 25/64	2.26	5
130	5 1/8	140	5 33/64	2.31	5
140	5 33/64	150	5 29/32	2.48	5
152	6	162	6 3/8	2.69	5
160	6 19/64	170	6 11/16	2.82	5
168	6 39/64	178	7	2.96	5
180	7 15/16	190	7 31/64	3.17	5
190	7 31/64	200	7 7/8	3.34	5
203	8	213	8 25/64	3.56	5
220	8 21/32	230	9 5/8	3.85	5
254	10	264	10 25/64	4.45	5
273	10 3/4	283	11 9/64	4.76	5
280	11 5/16	290	11 27/64	4.88	5
305	12	315	12 13/32	5.31	5
320	12 19/32	330	12 63/64	5.56	5
350	13 25/32	360	14 11/64	6.10	5
400	15 3/4	410	16 9/64	7.00	5
450	17 23/32	460	18 1/8	7.79	5
500	19 11/16	510	20 25/32	8.64	5
600	23 5/8	610	24 5/32	10.35	5

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.