

ABRASAND /10

SANDBLASTING HOSE



APPLICATION

Delivery hose, sand and bead blasting application

TUBE

Black, smooth, NR/SBR antistatic rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, antistatic cloth impression SBR/NR/PVC rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-40°F +158°F

-40°C +70°C

SPECIFICATIONS

DIN 53516 50 ± 5mm3

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
13	1/2	25	1	0.44	10	150	30	450	40
16	5/8	32	1 1/4	0.59	10	150	30	450	40
19	3/4	30	1 3/16	0.50	10	150	30	450	40/61
19	3/4	33	1 19/64	0.66	10	150	30	450	40/61
25	1	40	1 37/64	0.88	10	150	30	450	40/61
30	1 3/16	45	1 25/32	1.02	10	150	30	450	40/61
32	1 1/4	48	1 57/64	1.16	10	150	30	450	40/61
38	1 1/2	54	2 1/8	1.33	10	150	30	450	40/61
40	1 37/64	60	2 23/64	1.83	10	150	30	450	40/61
51	2	71	2 51/64	2.20	10	150	30	450	40/61
60	2 23/64	80	3 5/32	2.53	10	150	30	450	40/61
80	3 5/32	105	4 15/16	4.18	10	150	30	450	40/61
90	3 35/64	115	4 17/32	4.63	10	150	30	450	40/61
102	4	127	5	5.17	10	150	30	450	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

