

# ABRASAND HD /18

SANDBLASTING HEAVY DUTY HOSE



## APPLICATION

Delivery hose, sand and bead blasting application, high pressure, high abrasion resistance

## TUBE

Black, smooth, NR/SBR antistatic rubber compound

## REINFORCEMENT

High strength synthetic plies

## COVER

Black, smooth, antistatic cloth impression SBR/NR/PVC rubber compound, abrasion and weather resistant

## WORKING TEMPERATURE

-40°F +158°F

-40°C +70°C

## SPECIFICATIONS

DIN 53516 50 ± 5mm3

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
13	1/2	25	1	0.45	18	270	54	810	40
16	5/8	30	1 3/16	0.63	18	270	54	810	40
19	3/4	30	1 3/16	0.53	18	270	54	810	40/61
19	3/4	33	1 19/64	0.71	18	270	54	810	40/61
25	1	40	1 37/64	0.96	18	270	54	810	40/61
30	1 3/16	45	1 25/32	1.10	18	270	54	810	40/61
32	1 1/4	48	1 57/64	1.26	18	270	54	810	40/61
35	1 3/8	54	2 1/8	1.66	18	270	54	810	40/61
38	1 1/2	54	2 1/8	1.44	18	270	54	810	40/61
40	1 37/64	60	2 23/64	1.96	18	270	54	810	40/61
51	2	71	2 51/64	2.39	18	270	54	810	40/61
60	2 23/64	80	3 5/32	2.75	18	270	54	810	40/61
65	2 9/16	85	3 3/8	2.78	18	270	54	810	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

## BRANDING

