

ABRASTAR /12 HD36

SANDBLASTING HEAVY DUTY HOSE



APPLICATION

Delivery hose, sand and bead blasting application, high pressure, high abrasion resistance

TUBE

Black, smooth, **NR/SBR** antistatic rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, antistatic cloth impression **NR/SBR** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-40°F +158°F
-40°C +70°C

SPECIFICATIONS

DIN 53516 36 ± 5 mm³

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
19	3/4	33	1 19/64	0.71	12	180	36	540	40
25	1	40	1 37/64	0.96	12	180	36	540	40
32	1 1/4	48	1 57/64	1.26	12	180	36	540	40
38	1 1/2	56	2 13/64	1.44	12	180	36	540	40
38	1 1/2	60	2 23/64	1.48	12	180	36	540	40
51	2	71	2 51/64	2.39	12	180	36	540	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

