

AGRABREW SD /10

BEER SUCTION AND DELIVERY HOSE



APPLICATION

Suction and delivery hose for beer, wine, alcohol, soft drinks

TUBE

White, smooth **BIIR** (butyl) rubber compound, food quality odourless and taste free

REINFORCEMENT

High strength synthetic plies with steel wire spirals

COVER

Orange, smooth, cloth impression **EPDM** rubber, resistant to abrasion, ozone and weather

WORKING TEMPERATURE

-40 °F +248 °F sterilization at 230 °F for 30 minutes
-40 °C +120 °C sterilizzazione a 110 °C massimo 30'

SPECIFICATIONS

FDA title 21 art.177.2600 (e) for liquid foods, BfR, ADI free, PHTHALATE free, CE 1935/2004

| ID | | OD | | WEIGHT | WP | | BP | | BENDING RADIUS | VACUUM | COIL LENGTH |
|------|--------|-----|---------|--------|-----|-----|-----|-----|----------------|--------|-------------|
| mm | inch | mm | inch | kg/m | bar | psi | bar | psi | mm | bar | m |
| 19 | 3/4 | 32 | 1 1/4 | 0.78 | 10 | 150 | 30 | 450 | 80 | 0.9 | 40 |
| 25 | 1 | 38 | 1 1/2 | 0.92 | 10 | 150 | 30 | 450 | 115 | 0.9 | 40 |
| 32 | 1 1/4 | 45 | 1 25/32 | 1.19 | 10 | 150 | 30 | 450 | 145 | 0.9 | 40 |
| 38 | 1 1/2 | 50 | 1 31/32 | 1.48 | 10 | 150 | 30 | 450 | 180 | 0.9 | 40 |
| 51 | 2 | 64 | 2 17/32 | 1.87 | 10 | 150 | 30 | 450 | 245 | 0.9 | 40 |
| 63.5 | 2 1/2 | 80 | 3 5/32 | 2.68 | 10 | 150 | 30 | 450 | 340 | 0.9 | 40 |
| 65 | 2 9/16 | 82 | 3 15/64 | 2.85 | 10 | 150 | 30 | 450 | 350 | 0.9 | 40 |
| 76 | 3 | 92 | 3 5/8 | 3.23 | 10 | 150 | 30 | 450 | 410 | 0.9 | 40 |
| 102 | 4 | 120 | 4 23/32 | 4.70 | 10 | 150 | 30 | 450 | 580 | 0.9 | 40 |

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

