

# AGRAVAP 6 L/L

FDA WASHDOWN HOSE



## APPLICATION

Washdown hose for food industry floors and equipments

## TUBE

White, smooth **NBR** rubber compound, food quality odourless and taste free

## REINFORCEMENT

High strength synthetic plies

## COVER

Blue, smooth, cloth impression **NBR/PVC** rubber, resistant to abrasion, ozone and weathering

## WORKING TEMPERATURE

Hot water -40°F +212°F

Steam max +327°F

Acqua calda -40°C +100°C

Vapore max +164°C

## SPECIFICATIONS

FDA title 21, art.177.2600 for aqueous foods, BfR

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	m
13	1/2	23	29/32	0,35	6	90	60	900	65	40
16	5/8	26	1 1/32	0,45	6	90	60	900	85	40
19	3/4	31	1 7/32	0,60	6	90	60	900	100	40
25	1	37	1 29/64	0,80	6	90	60	900	125	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

## BRANDING

TGT AGRAP W.P. 6 BAR FDA-BfR ITALY