

AQUADEL /10

WATER DELIVERY HOSE



APPLICATION

Delivery hose for air water and not corrosive inert fluids for general industrial applications. Very strong and flexible structure

TUBE

Black, smooth, **SBR** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, cloth impression **SBR** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-22°F +176°F
-30°C +80°C

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
22	7/8	30	1 3/16	0.42	10	150	30	450	40
25	1	35	1 3/8	0.64	10	150	30	450	40/61
28	1 7/64	38	1 1/2	0.66	10	150	30	450	40/61
30	1 3/16	41	1 5/8	0.98	10	150	30	450	40/61
32	1 1/4	44	1 47/64	1.02	10	150	30	450	40/61
35	1 3/8	47	1 27/32	1.10	10	150	30	450	40/61
38	1 1/2	50	1 31/32	1.18	10	150	30	450	40/61
40	1 37/64	54	2 1/8	1.48	10	150	30	450	40/61
45	1 25/32	59	2 21/64	1.62	10	150	30	450	40/61
51	2	65	2 9/16	1.67	10	150	30	450	40/61
60	2 23/64	74	2 59/64	3.28	10	150	30	450	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

