

# CALORAD

## RADIATOR HOSE



### APPLICATION

Delivery hose for hot water and coolant fluids, applied in engine cooling and heating system. Radiator hose

### TUBE

Black, smooth, **EPDM** rubber compound

### REINFORCEMENT

High strength synthetic plies

### COVER

Black, smooth, cloth impression **EPDM** rubber compound, abrasion, ozone and weather resistant

### WORKING TEMPERATURE

-40°F +248°F

-40°C +120°C

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
13	1/2	19	3/4	0.20	3	45	10	150	1/40
16	5/8	22	7/8	0.25	3	45	10	150	1/40
18	45/64	24	61/64	0.28	3	45	10	150	1/40
20	25/32	26	1 5/16	0.30	3	45	10	150	1/40/61
22	7/8	28	1 7/64	0.32	3	45	10	150	1/40/61
25	1	32	1 1/4	0.42	3	45	10	150	1/40/61
28	1 7/64	36	1 27/64	0.47	3	45	10	150	1/40/61
30	1 3/16	38	1 1/2	0.53	3	45	10	150	1/40/61
32	1 1/4	40	1 37/64	0.57	3	45	10	150	1/40/61
35	1 3/8	43	1 45/64	0.61	3	45	10	150	1/40/61
38	1 1/2	47	1 27/32	0.75	3	45	10	150	1/40/61
40	1 37/64	49	1 15/16	0.86	3	45	10	150	1/40/61
42	1 21/32	51	2	0.90	3	45	10	150	1/40/61
45	1 25/32	54	2 1/8	0.92	3	45	10	150	1/40/61
48	1 57/64	58	2 9/32	1.04	3	45	10	150	1/40/61
51	2	61	2 13/32	1.10	3	45	10	150	1/40/61
55	2 11/64	65	2 9/16	1.18	3	45	10	150	1/40/61
60	2 23/64	70	2 3/4	1.28	3	45	10	150	1/40/61
65	2 9/16	75	2 61/64	1.37	3	45	10	150	1/40/61
70	2 3/4	80	3 5/32	1.47	3	45	10	150	1/40/61
76	3	86	3 25/64	1.59	3	45	10	150	1/40/61
80	3 5/32	92	3 5/8	1.90	3	45	10	150	1/40/61
90	3 35/64	102	4	2.15	3	45	10	150	1/40/61
102	4	113	4 29/64	2.35	3	45	10	150	1/40/61
110	4 21/64	123	4 27/32	2.50	3	45	10	150	1/40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

### BRANDING

