

CALORDIN

RADIATOR HOSE DIN 73411-79



APPLICATION

Delivery hose for hot water and coolant fluids, applied in engine cooling and heating system. Radiator hose

TUBE

Black, smooth, EPDM rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, cloth impression EPDM rubber compound, abrasion, ozone and weather resistant

WORKING TEMPERATURE

-40°F +248°F

-40°C +120°C

SPECIFICATIONS

DIN 73411:79

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
18	45/64	25	1	0.30	4	60	12	180	1/40
20	25/32	27	1 5/8	0.32	4	60	12	180	1/40/61
22	7/8	29	1 9/64	0.35	4	60	12	180	1/40/61
25	1	33	1 19/64	0.42	4	60	12	180	1/40/61
28	1 7/64	36	1 27/64	0.47	4	60	12	180	1/40/61
30	1 3/16	38	1 1/2	0.53	4	60	12	180	1/40/61
32	1 1/4	40	1 37/64	0.57	4	60	12	180	1/40/61
35	1 3/8	43	1 45/64	0.61	4	60	12	180	1/40/61
38	1 1/2	47	1 27/32	0.75	4	60	12	180	1/40/61
40	1 37/64	50	1 31/32	0.88	4	60	12	180	1/40/61
42	1 21/32	52	2 15/32	0.92	4	60	12	180	1/40/61
45	1 25/32	55	2 11/64	0.98	4	60	12	180	1/40/61
48	1 57/64	58	2 9/32	1.04	4	60	12	180	1/40/61
51	2	61	2 13/32	1.10	4	60	12	180	1/40/61
55	2 5/32	65	2 9/16	1.18	4	60	12	180	1/40/61
60	2 23/64	70	2 3/4	1.28	4	60	12	180	1/40/61
65	2 9/16	75	2 61/64	1.37	4	60	12	180	1/40/61
70	2 3/4	80	3 5/32	1.47	4	60	12	180	1/40/61
76	3	86	3 25/64	1.59	4	60	12	180	1/40/61
80	3 5/32	92	3 5/8	1.90	4	60	12	180	1/40/61
90	3 35/64	102	4	2.15	4	60	12	180	1/40/61
102	4	114	4 31/64	2.54	4	60	12	180	1/40/61
110	4 21/64	124	4 7/8	2.65	4	60	12	180	1/40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

