

CALORFIGHTER SW 300

FIREWATER DELUGE HOSE-ABS APPROVED



APPLICATION

Delivery hose for firewater deluge hose application on oil rigs

TUBE

Black, smooth, CR rubber

REINFORCEMENT

High strength steel cord

COVER

Glassfiber layers, co-vulcanized with an external layer of red CR rubber compound, fire, sea water, abrasion and ozone resistant

WORKING TEMPERATURE

-40°F +212°F

-40°C +100°C

SPECIFICATIONS

EN 15540:1999 (800°C X 30') / PDA ABS Nr. 16-GE1577500-PDA

| ID | | OD | | WEIGHT | WP | | BP | | BENDING RADIUS | COIL LENGTH |
|-----|------|-----|---------|--------|-----|-----|-----|------|----------------|-------------|
| mm | inch | mm | inch | kg/m | bar | psi | bar | psi | mm | m |
| 51 | 2 | 80 | 3 5/32 | 4.90 | 20 | 300 | 100 | 1500 | 420 | 60 |
| 76 | 3 | 108 | 4 15/64 | 7.50 | 20 | 300 | 100 | 1500 | 535 | 60 |
| 102 | 4 | 134 | 5 9/32 | 11.00 | 20 | 300 | 100 | 1500 | 640 | 60 |
| 127 | 5 | 160 | 6 19/64 | 13.40 | 20 | 300 | 100 | 1500 | 1100 | 60 |
| 152 | 6 | 185 | 7 9/32 | 15.70 | 20 | 300 | 100 | 1500 | 1210 | 60 |

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

