

CALORFOOD 120°C FDA L/L

FDA LONG LENGTH HOT WATER HOSE



APPLICATION

Delivery hose for potable hot water and detergents. Used for industrial washing machines; recommended for washdown use in poultry farms and dairies

TUBE

White, smooth, food quality **EPDM** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Blue, smooth, **EPDM** rubber compound, abrasion, ozone and weather resistant (other colors on demand)

WORKING TEMPERATURE

-40°F +248°F

-40°C +120°C

SPECIFICATIONS

FDA title 21, art.177.2600 for aqueous foods

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
6	1/4	12	15/32	0.13	10	150	30	450	MAX 100
6	1/4	13	1/2	0.14	10	150	30	450	MAX 100
8	5/16	15	19/32	0.17	10	150	30	450	MAX 100
10	13/32	17	43/64	0.18	10	150	30	450	MAX 100
11	7/16	19	3/4	0.20	10	150	30	450	MAX 100
12	15/32	19.5	49/64	0.23	10	150	30	450	MAX 100
13	1/2	23	29/32	0.25	10	150	30	450	MAX 100

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

TGT CALORFOOD W.P. 10 BAR FDA ITALY