

CALORFOOD 120°C FDA L/L

FDA LONG LENGTH HOT WATER HOSE



APPLICATION

Delivery hose for potable hot water and detergents. Used for industrial washing machines; recommended for washdown use in poultry farms and dairies

TUBE

White, smooth, food quality **EPDM** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Blue, smooth, **EPDM** rubber compound, abrasion, ozone and weather resistant (other colors on demand)

WORKING TEMPERATURE

-40°F +248°F

-40°C +120°C

SPECIFICATIONS

FDA title 21, art.177.2600 for aqueous foods

| ID | | OD | | WEIGHT | WP | | BP | | COIL LENGTH |
|----|-------|------|-------|--------|-----|-----|-----|-----|-------------|
| mm | inch | mm | inch | kg/m | bar | psi | bar | psi | m |
| 6 | 1/4 | 12 | 15/32 | 0.13 | 10 | 150 | 30 | 450 | MAX 100 |
| 6 | 1/4 | 13 | 1/2 | 0.14 | 10 | 150 | 30 | 450 | MAX 100 |
| 8 | 5/16 | 15 | 19/32 | 0.17 | 10 | 150 | 30 | 450 | MAX 100 |
| 10 | 13/32 | 17 | 43/64 | 0.18 | 10 | 150 | 30 | 450 | MAX 100 |
| 11 | 7/16 | 19 | 3/4 | 0.20 | 10 | 150 | 30 | 450 | MAX 100 |
| 12 | 15/32 | 19.5 | 49/64 | 0.23 | 10 | 150 | 30 | 450 | MAX 100 |
| 13 | 1/2 | 23 | 29/32 | 0.25 | 10 | 150 | 30 | 450 | MAX 100 |

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

TGT CALORFOOD W.P. 10 BAR FDA ITALY