

# CALORSTAR R /210°C ISO6134 2B

STEEL WIRE REINFORCEMENT STEAM HOSE 17 BAR - ISO 6134 -2B



## APPLICATION

Delivery hose for high pressure saturated steam, suitable for tanks and pipelines steam cleaning in the petrochemical industry. Oil resistant cover

## TUBE

Black, smooth, EPM rubber compound

## REINFORCEMENT

High tensile strength steel reinforcements

## COVER

Red, smooth, pin pricked, cloth impression EPM rubber compound, abrasion, oil, ozone and weather resistant

## WORKING TEMPERATURE

-40°F +410°F peaks 450°F  
-40°C +210°C picchi 232°C

## SPECIFICATIONS

ISO 6134 - TYPE 2 CLASS B

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	m
13	1/2	25	1	0.53	18	270	180	2700	120	40/61
16	5/8	30	1 3/16	0.75	18	270	180	2700	155	40/61
19	3/4	33	1 19/64	0.78	18	270	180	2700	185	40/61
25	1	40	1 37/64	1.02	18	270	180	2700	240	40/61
32	1 1/4	48	1 57/64	1.41	18	270	180	2700	330	40/61
38	1 1/2	54	2 1/8	1.77	18	270	180	2700	390	40/61
51	2	69	2 23/32	2.58	18	270	180	2700	520	40/61
63	2 1/2	81	3 3/16	3.16	18	270	180	2700	640	40/61
76	3	94	3 45/64	4.01	18	270	180	2700	745	40/61
102	4	122	4 51/64	6.21	18	270	180	2700	990	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

## BRANDING

