

CHEMIBLUE D /20

UREA DELIVERY HOSE / ADBLUE® PRODUCTS



APPLICATION

Delivery hose for urea ADBLUE® based fluid used in ECO fuels engines

TUBE

Black, smooth **EPDM** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, cloth impression **EPDM** rubber compound, resistant to abrasion, ozone and weather

WORKING TEMPERATURE

-40°F +212°F

-40°C +100°C

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	m
13	1/2	23	29/32	0.42	20	300	60	900	100	50 L/L
19	3/4	32	1 1/4	0.60	20	300	60	900	120	50 L/L
25	1	39	1 17/32	0.88	20	300	60	900	150	50 L/L
32	1 1/4	42	1 21/32	1.12	20	300	60	900	200	40/61
38	1 1/2	50	1 31/32	1.32	20	300	60	900	230	40/61
51	2	67	2 41/64	1.85	20	300	60	900	305	40/61
63.5	2 1/2	75	2 61/64	2.15	20	300	60	900	390	40/61
76	3	92	3 5/8	2.70	20	300	60	900	460	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

