

# MARINEGEN ISO 7840 A1

FUEL DELIVERY HOSE ON LEISURE BOATS



## APPLICATION

Delivery hose for diesel, bio diesel fuel and for eco gasoline, for marine engines installed on leisure boats (up to 24m)

## TUBE

Black, smooth, **NBR** rubber compound

## REINFORCEMENT

High strength synthetic plies, with 1 crossing copper wire for hose grounding

## COVER

Black, smooth, cloth impression **CR** rubber compound, self extinguishing, resistant to heat, fuels, and weather

## WORKING TEMPERATURE

-4°F +212°F

-20°C +100°C

## SPECIFICATIONS

ISO 7840:2004 A1 CE, approved RINA DIP 63797, SAE J 1527:2004 A1

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
19	3/4	32	1 1/4	0.75	10	150	30	450	40
25	1	39	1 17/32	0.95	10	150	30	450	40/61
30	1 3/16	44	1 47/64	1.15	10	150	30	450	40/61
32	1 1/4	46	1 13/16	1.24	10	150	30	450	40/61
38	1 1/2	52	2 15/32	1.55	10	150	30	450	40/61
40	1 37/64	54	2 1/8	1.61	10	150	30	450	40/61
45	1 25/32	59	2 21/64	1.80	10	150	30	450	40/61
51	2	65	2 9/16	1.95	10	150	30	450	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

## BRANDING

