

MARINESAN SD /10 EN ISO 8099

WATER SUCTION AND DELIVERY HOSE FOR TOILETTES ON LEISURE BOATS



APPLICATION

Suction and delivery hose for sanitary equipments installed on board of leisure boats. Completely smells shielded

TUBE

White, smooth **BIIR** (butyl) rubber compound, food quality odourless and taste free

REINFORCEMENT

High strength synthetic plies with steel wire spirals

COVER

White, smooth, cloth impression **EPDM** rubber, resistant to abrasion, ozone and weather

WORKING TEMPERATURE

-40°F +248°F
-40 °C+120 °C

SPECIFICATIONS

EN ISO 8099

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	VACUUM	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	bar	m
19	3/4	29	1 9/64	0.72	10	150	30	450	80	0.9	40
25	1	35	1 3/8	0.87	10	150	30	450	115	0.9	40
38	1 1/2	48	1 57/64	1.80	10	150	30	450	180	0.9	40
40	1 37/64	50	1 31/32	2.00	10	150	30	450	180	0.9	40
45	1 25/32	55	2 11/64	2.25	10	150	30	450	200	0.9	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

