

MARINESPIR ISO7840 A1

FUEL SUCTION AND DELIVERY HOSE ON LEISURE BOATS



APPLICATION

Suction and delivery hose for diesel, bio diesel fuel and for eco gasoline, for marine engines installed on leisure boats (up to 24m)

TUBE

Black, smooth, **NBR** rubber compound

REINFORCEMENT

High strength synthetic plies, with 1 crossing copper wire for hose grounding

COVER

Black, smooth, cloth impression **CR** rubber compound, self extinguishing, resistant to heat, fuels, and weather

WORKING TEMPERATURE

-4 °F +212 °F

-20 °C +100 °C

SPECIFICATIONS

ISO 7840:2004 A1 CE, approved RINA DIP 22802/CS, SAE J 1527:2004 A1

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	VACUUM	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	bar	m
19	3/4	29	1 9/64	0.64	5	75	15	225	70	0.9	40
20	25/32	30	1 3/16	0.68	5	75	15	225	75	0.9	40 /61
25	1	35	1 3/8	0.80	5	75	15	225	95	0.9	40 /61
30	1 3/16	40	1 37/64	0.96	5	75	15	225	115	0.9	40 /61
32	1 1/4	42	1 21/32	0.98	5	75	15	225	125	0.9	40 /61
38	1 1/2	48	1 57/64	1.14	5	75	15	225	150	0.9	40 /61
51	2	61	2 13/32	1.50	5	75	15	225	210	0.9	40 /61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

