

MULTIPURPOSE SD/ 10

MULTIPURPOSE SUCTION AND DELIVERY EPDM HOSE



APPLICATION

Suction and delivery hose for multiple use as, chemicals, hot water and sea water

TUBE

Black, smooth, **EPDM** rubber compound

REINFORCEMENT

High strength synthetic plies with steel wire spirals

COVER

Black, smooth, cloth impression **EPDM** rubber, resistant to heat, sea water and weather

WORKING TEMPERATURE

-40 °F +248 °F
-40 °C +120 °C

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	VACUUM	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	bar	m
13	1/2	23	29/32	0.41	10	150	30	450	80	0.9	40
16	5/8	26	1 5/16	0.50	10	150	30	450	90	0.9	40
18	45/64	28	1 7/64	0.52	10	150	30	450	110	0.9	40
19	3/4	29	1 9/64	0.53	10	150	30	450	115	0.9	40
20	25/32	30	1 3/16	0.55	10	150	30	450	120	0.9	40
25	1	35	1 3/8	0.70	10	150	30	450	150	0.9	40
30	1 3/16	40	1 37/64	0.78	10	150	30	450	180	0.9	40
32	1 1/4	43	1 45/64	0.95	10	150	30	450	190	0.9	40
35	1 3/8	46	1 13/16	1.09	10	150	30	450	210	0.9	40
38	1 1/2	49	1 15/16	1.21	10	150	30	450	230	0.9	40
40	1 37/64	51	2	1.30	10	150	30	450	240	0.9	40
45	1 25/32	57	2 1/4	1.62	10	150	30	450	270	0.9	40
51	2	63	2 31/64	1.77	10	150	30	450	310	0.9	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

