

# PETROBUNKER SW /15

BUNKERING DELIVERY HOSE FOR PETROLEUM PRODUCTS



## APPLICATION

Delivery hose for bunkering and docks service for the transfer of crude oil and mixed fuels with aromatic contents up to 50%

## TUBE

Black, smooth, **NBR** rubber compound

## REINFORCEMENT

High strength synthetic cord, with 2 crossing copper wires for hose grounding

## COVER

Black, smooth cloth impression, **CR** rubber compound, resistant to oil, grease, sea water, ozone and flame retardant

## WORKING TEMPERATURE

-22°F +212°F

-30°C +100°C

## SPECIFICATIONS

BS 1435:1987 L15 / UNI EN 1765:99 L15

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
51	2	63.5	2 1/2	1.80	15	225	60	900	60
76	3	94	3 45/64	4.05	15	225	60	900	60
102	4	122	4 51/64	6.50	15	225	60	900	60
127	5	147	5 25/32	7.05	15	225	60	900	60
152	6	176	6 15/16	8.20	15	225	60	900	60
203	8	230	9 5/8	9.70	15	225	60	900	40
254	10	284	11 3/16	12.40	15	225	60	900	20
302	12	340	13 25/64	15.00	15	225	60	900	12

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

## BRANDING

