

# PETROCAR 10 LT-Ω

FUEL AND MINERAL OIL DELIVERY HOSE - LONG LENGTH



## APPLICATION

Delivery hose for mineral oils, diesel fuel and gasoline with aromatic contents up to 50%

## TUBE

Black, smooth, conductive **NBR** rubber compound ( $R \leq 1M\Omega$ )

## REINFORCEMENT

High strength synthetic plies

## COVER

Black, smooth, conductive **NBR/PVC** rubber compound, resistant to oils, fuels, ozone and weathering ( $R \leq 1M\Omega$ )

## WORKING TEMPERATURE

-40°F +212°F

-40°C +100°C

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	m
4	5/32	10	3/8	0,10	10	150	30	450	40	100
5	3/16	12	15/32	0,12	10	150	30	450	40	100
6	1/4	13	1/2	0,14	10	150	30	450	50	100
7	9/32	13	1/2	0,13	10	150	30	450	60	100
8	5/16	15	19/32	0,17	10	150	30	450	65	100
10	3/8	17	43/64	0,20	10	150	30	450	80	100
13	1/2	20	25/32	0,24	10	150	30	450	105	50
15	19/32	23	29/32	0,32	10	150	30	450	120	50
19	3/4	27	1 1/16	0,37	10	150	30	450	150	50
25	1	35	1 3/8	0,61	10	150	30	450	200	50

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

## BRANDING

TGT PETROCAR W.P. 10 BAR  $R \leq 1M\Omega$  ITALY