

# PETROCAR 20 L/L

FUEL AND MINERAL OIL DELIVERY HOSE - LONG LENGTH



## APPLICATION

Delivery hose for mineral oils, diesel fuel and gasoline with aromatic contents up to 50%

## TUBE

Black, smooth, **NBR** rubber compound

## REINFORCEMENT

High strength synthetic plies

## COVER

Black, smooth, **NBR/PVC** rubber compound, resistant to oils, fuels, ozone and weather

## WORKING TEMPERATURE

-13°F +176°F

-25°C +80°C

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	m
5	3/16	13	1/2	0.09	20	300	60	900	40	100
6	1/4	14	9/16	0.15	20	300	60	900	50	100
8	5/16	15	19/32	0.17	20	300	60	900	60	100
8	5/16	17	43/64	0.18	20	300	60	900	65	100
10	3/8	17	43/64	0.20	20	300	60	900	75	100
10	3/8	19	3/4	0.22	20	300	60	900	80	100
13	1/2	21	53/64	0.25	20	300	60	900	95	50
13	1/2	23	29/32	0.27	20	300	60	900	105	50
16	5/8	26	1 5/16	0.35	20	300	60	900	120	50
19	3/4	29	1 9/64	0.40	20	300	60	900	140	50
19	3/4	30	1 3/16	0.42	20	300	60	900	145	50
25	1	36	1 27/64	0.64	20	300	60	900	200	50

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

## BRANDING

TGT PETROCAR W.P. 20 BAR ITALY