


# SILAR

WATER COOLING DELIVERY HOSE FOR HIGH TEMPERATURES



## APPLICATION

Delivery hose for hot water and coolant fluid, applied in engine cooling systems where resistance to high working temperature is required

## TUBE

Red, smooth, **VMQ** silicon (available also in many other colors)

## REINFORCEMENT

NOMEX fibers

## COVER

Red, smooth, cloth impression silicon **VMQ**, high temperature and weather resistant (available also in many other colors)

## WORKING TEMPERATURE

-76 °F +482 °F

-60 °C +250 °C

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
12	15/32	22	7/8	0.30	5	75	15	225	1/20
18	45/64	28	1 7/64	0.38	5	75	15	225	1/20
20	25/32	30	1 3/16	0.43	5	75	15	225	1/20
22	7/8	32	1 1/4	0.46	5	75	15	225	1/20
25	1	35	1 3/8	0.50	5	75	15	225	1/20
28	1 7/64	38	1 1/2	0.54	5	75	15	225	1/20
30	1 3/16	40	1 37/64	0.60	5	75	15	225	1/20
32	1 1/4	42	1 21/32	0.64	5	75	15	225	1/20
35	1 3/8	45	1 25/32	0.68	5	75	15	225	1/20
38	1 1/2	48	1 57/64	0.70	5	75	15	225	1/20
40	1 37/64	50	1 31/32	0.74	5	75	15	225	1/20
42	1 21/32	52	2 15/32	0.78	5	75	15	225	1/20
45	1 25/32	55	2 11/64	0.83	5	75	15	225	1/20
48	1 57/64	58	2 9/32	0.88	5	75	15	225	1/20
50	1 31/32	60	2 3/8	0.93	5	75	15	225	1/20
51	2	61	2 13/32	0.94	5	75	15	225	1/20
55	2 11/64	65	2 9/16	0.98	4	60	12	180	1/20
60	2 3/8	70	2 3/4	1.10	4	60	12	180	1/20
63.5	2 1/2	73.5	2 57/64	1.19	4	60	12	180	1/20
70	2 3/4	80	3 5/32	1.28	4	60	12	180	1/20
76	3	86	3 25/64	1.40	4	60	12	180	1/20
80	3 5/32	90	3 35/64	1.45	4	60	12	180	1/20
90	3 35/64	100	3 15/16	2.01	4	60	12	180	1/20
102	4	112	4 13/32	2.30	4	60	12	180	1/20

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.