

# WELTWIN 20 ISO3821 L/L

WELDING HOSE - TWIN



## APPLICATION

Delivery twin hose, oxygen/acetylene line for welding equipments

## TUBE

Black, smooth, **SBR** rubber compound

## REINFORCEMENT

High strength synthetic plies

## COVER

Blue and Red, smooth, **SBR/EPDM** rubber compound, abrasion and weather resistant

## WORKING TEMPERATURE

-13°F +176°F

-25°C +80°C

## SPECIFICATIONS

ISO 3821

| ID  |              | OD |       | WEIGHT | WP  |     | BP  |     | COIL LENGTH |
|-----|--------------|----|-------|--------|-----|-----|-----|-----|-------------|
| mm  | inch         | mm | inch  | kg/m   | bar | psi | bar | psi | m           |
| 6+6 | 1/4 +1/4     | 13 | 1/2   | 0.35   | 20  | 300 | 60  | 900 | 50/100      |
| 8+8 | 5/16 +5/16   | 15 | 19/32 | 0.40   | 20  | 300 | 60  | 900 | 50/100      |
| 9+9 | 23/64 +23/64 | 16 | 5/8   | 0.43   | 20  | 300 | 60  | 900 | 50/100      |

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

## BRANDING

TGT WELTWIN W.P. 20 BAR ISO 3821 ITALY